

PuREPower 15.0 Lite

Specification Sheet

MODEL	PuREPower 15.0 Lite(3P/3P)
Rated Power	15000 W
INPUT	
Voltage	3 x 415 VAC
Selectable Volatage Range	380 - 440 VAC
Frequency Range	50 Hz/60 Hz (Auto sensing)
OUTPUT	
AC Voltage Regulation (Battery Mode)	415VAC $\pm$ 5%
Surge Power	24000VA
Efficiency (Peak)	~~ 94%
Switching Modes	On Grid /Off Grid/Hybrid(Optional)
Transfer Time	10 ms
Waveform	Pure sine wave
SOLAR CHARGER & AC CHARGER	
Solar Charger Type	MPPT
No. of MPPTs	3
Maximum PV Array Open Circuit Voltage	450 VDC
Maximum PV Array Power	3 X 8500W
Maximum PV Input Current	3 X 27 A
MPP Range @ Operating Voltage	60~ 450VDC
Maximum Solar Charge Current	360A
Maximum AC Charge Current	360A
Maximum Charge Current	360A
BATTERY	
Battery Cell Technology	Lithium Ion
Nominal Voltage	48V
Battery Capacity (KWh)	12
Max. Continuous charging Current	60A
Max. Continuous Discharging Current	90A X 3
Full Charging Voltage	54.3V
Quantity of Batteries	3 Nos

PROTECTION

Protection	5th Gen BMS,DC breaker
Anti-islanding Protection	Integrated
AC Over Current Protection	Integrated
Output short circuit	Integrated
Overload Protection	Integrated
Battery voltage too low	Integrated
Temperature too high	Integrated
Input voltage out of range/Ripple too high	Integrated
Fan block	Integrated
IP Protection	IP54

GENERAL DATA

Dimension, L x W x H (mm)	(510 x 524 x 1131)
Cooling concept	Advanced Nano PCM combined with forced convec-
LCD display with indicators	Operating mode/load/input/output, etc
PV connection	MC4 connector
AC connection	Terminal connectors
No.of AC Output	1
Topology	High frequency isolation
Installation Style	Floor standing
Operating Temperature Range	-10°C ~ 60°C*
Noise	<50dB
Warranty	5 years
Extended Warranty	12 years
Net Weight (kg)	150 Kgs
Communication Interface	BMS, Dry-contact, CAN, Bluetooth, Wi-Fi, AI Cloud
Certifications	BIS Certified (R-63005436) IS 16221 (PART 2): 2015/ IEC 62109-2: 2011 AND IS 16169: 2019/ IEC 62116: 2014 AND IS 17980: 2022/